

Pozicija 1.

Constant Back Pressure Regulator Fisher 611EDR / Masoneilan 526-50

Fluid: Oil

3" 300# ANSI RF

WCB steel body

Cage guiding trim

2 5/16" port size

Quick opening plug

416SS trim material

Plain bonnet, TFE packing

Actuator with 210-255 PSI range set to maintain 250 PSI dP

Cv = 4.5 – 35.2

Travel ¼"

Pozicija 2.

Lube Oil Pressure Regulator Fisher 655ED

Fluid: Lube Oil

3" 300# ASA RF

SS trim

Full port trim – Quick opening

max dP=550 PSI

Standard bonnet

Teflon packing

Diaphragm actuator #42

Increase pressure to close

12-36 psig diaphragm spring; max casing pressure 100 psi

Valve set to maintain 20 psig at compressor lube oil header

Rated Cv = 8 – 50

Travel 7/16"

Pozicija 3.

Lube Oil Pressure Regulator Fisher 655ED

Fluid: Lube Oil

2" 300# ASA RF

SS trim

Cage trim – Full Quick opening

max dP=550 PSI

Standard bonnet

Teflon packing

Diaphragm actuator #42

Increase pressure to close

12-36 psig diaphragm spring

Valve set to maintain 20 psig at compressor lube oil header

Rated Cv = 7.5 - 28